

TradeWinds International, Inc.

KRYSTALKOTE™

Limited Warranty of Performance

TradeWinds International, Inc., hereby offers a limited warranty of performance on **KrystalKote™**, a two-component, US DA- & CalTrans-Approved, EPA & SCAQMD VOC-compliant, high-solids, anti-graffiti, aliphatic polyurethane coating, according to the following criteria:

- A. Adherence to conditions and directions, as described in the **KrystalKote™ Data Sheet**, concerning proper surface preparation; material mixing & application; and observation of proper cure time, prior to allowable use conditions.
- B. Exposure to U-V, weather, limited chemical & physical contact, and normal conditions of use, with noted restrictions and qualifications, as described in the **KrystalKote™ Data Sheet**.
- C. Quality of application, quality of components, chemical make-up and physical condition of any underlying coatings, whether previously or newly applied, must be thoroughly tested and documented, for proper compatibility, prior to any proposed overlaying application of **KrystalKote™**. Any and all evidence of non-compatibility, poor condition of undercoat, or lack of proper surface preparation, gathered prior or subsequent to over-coating, will void any suggested, implied, or written warranty concerning any overlaying application of **KrystalKote™**.

TradeWinds International, Inc., with above cited qualifications and conditions, hereby warrants the following guarantees of performance, with liability not to exceed the warranted product replacement cost or actual replacement of the warranted product:

- 1. **KrystalKote™/KrystalTred™ Custom gloss, semi-gloss, satin, or flat** finishes, are warranted against fading (loss of color) greater than ten percent (10%) of original color tone or hue, due to U-V exposure and normal effects of weathering, for a period of ten (10) years.
- 2. **KrystalKote™ Clear gloss** is also warranted to protect underlying color coats from fading (loss of color) greater than ten percent (10%) of original color tone or hue, due to U-V exposure and normal effects of weathering, for a period of ten (10) years. **KrystalKote™ Clear gloss** is further warranted against noticeable yellowing from U-V exposure, for a period of ten (10) years.